IMPROVED Township_CANAAN	MADISO	7 - Du N CO. R 36-	▲	Secping Point
Class of Traffic	***************************************	Distance		
Built by	***************************************	Date	875.8 \0.89	Price \$
Surveyed by J. Converse				
BRICK: Kind of foundation Thickness of foundation Make of brick Width Crown Cushion Filler Kind of curb Size of curb X I yds brick Cu. yds of base	CONCRE Thickness Kind of Cement Mixture Material Slag Stone Width Crown Kind of expansion joints Cu. yds. concrete		SLAG—LIMESTONE Filler	Width 10'8.13' Crown 4 Cû. yds. Mat.
Total length	No	o. of steel br o. concrete o. of cor. pi	to berm 28 822 culverts culverts cen changed No.	Width of R. W. 40 & 50 No. Con. bridges No. of wood bridges Total excavation Location on R. W. Sile

INSPECTION OF IMPROVED ROADS.

	,		!
		••	
·			
		3	
2-			
<u> </u>			
	<u> </u>		
	1		1
\m	Shub Ol I	Com a Val F 157	Signam Amille E.)
1889	"Millikin Rd. Im	p." Rd. Imp. Mec. No. 2	p.128 (" W)
	Improved 1875 6		Improved 1875 See "Slut Rd. Imp." Com J. Vol. E. p. 171 1889 "Millikin Rd. Imp. Rd. Imp. Rec. No. 2

Illered