

MADISON COUNTY HIGHWAYS

NO. <u>15</u>	SECTION (S) <u>A</u>	NAME <u>Charleston - Chillicothe</u>
FROM <u>Clark Co Line</u> TO <u>Junction of SR #323</u>		
LENGTH <u>20381 21331</u> (IN FEET) MILES <u>3.86 4.04</u>		
PAVEMENT TYPE <u>Bit Surf Treated</u> WIDTH <u>16'</u>		
WIDTH OF R OF W <u>40'</u> WIDTH OF BERMS <u>3'</u>		
TWP. <u>Stokes</u> FEET <u>404</u>	MILES <u>3.86</u> TWP. <u></u>	FEET <u></u>
	MILES <u></u> TWP. <u></u>	FEET <u></u>
REMARKS <u>Road runs with C-16 for .42 mile</u>		

COUNTY ROAD HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	<u>RR #1</u>		<u>pg 40</u>	<u>Laid out 1833 see Thomas Rd</u>
		<u>Com/Vol B</u>		<u>Altered</u>

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
<u>1952</u>	<u>Asph 2" 6 stone</u>	<u>County</u>	<u>Surface treated from Clark Co line to *C-16</u>
<u>1954</u>	<u>Asph 2" 46 stone</u>	<u>County</u>	<u>Gravel road from C-16 to SR #323 built up to 8" base and black topped.</u>

IMPROVEMENTS Cont.

YEAR	TYPE OF	APPLIED BY	REMARKS
1956	Turq #46 stone	County	Surface treated from Jct CR #18 to SR #323
1958	MC3 #6 stone	"	Spot sealed
1959	MC5 #6 stone	"	Surface treated
MAY 1960	T-35	"	BROKEN PARTS OF ROAD REPAIRED AND SPOT TREATED
1962	MC-5 #6 stone	"	Surface treated
1964	MC-5 #6 stone	"	" "
1967	R. 51 #6 stone	COUNTY	SURFACE TREATED
1970	TAR #8 stone	COUNTY	SURFACE TREATED
1973	RS25 #8 GRAVEL	COUNTY	SURFACE TREATED
1976	RS2 #8	County	12,695 GAL RS2 + 436,90 ton #8 . 3.5
1980	586.40 ton #8 174.38 gal. RS2	County W. K. W.	Surface treated
1982	552.00 ton #8 10,634 Gal. RS2	County	Surface treated
1984	644 ton #8 12,706 Gal. RS2	Koch-W. K. W.	Surface Treated
1987	514.15 TONS #8 15,819 GAL. RS2	COUNTY & CENTRAL OIL	SURFACE TREATED
1990	11,148.18 gal. liquid asphalt 484 tons #8	County	Surface treated - entire road A & B sections
1995	CRS2P-#8 stone	County Road Crew	17,493.99 Gal - 620 Ton, Chip Seal - Resurface
1999	Cut off Hump @ Co. Line	Clark Co / Mad Co.	

MADISON COUNTY HIGHWAYS

NO. <u>15</u>	SECTION(S) <u>13</u>	NAME <u>Charles ton - Chillicothe Rd</u>
FROM <u>SR #323</u>		TO <u>Fayette Co line</u>
LENGTH <u>14098 15946</u> (IN FEET) MILES <u>2.67 3.02</u>		
PAVEMENT TYPE <u>Bit. Surf. treated</u>		WIDTH <u>16'</u>
WIDTH OF R OF W <u>40</u>		WIDTH OF BERMS <u>3'</u>
FEET <u>14098</u>		FEET <u></u>
TWP. <u>2 Stokes</u>	MILES <u>2.67</u>	TWP. <u>Range</u> MILES <u>1.98</u>
REMARKS <u>Road black topped and base built up to 8"</u>		

COUNTY ROAD HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	<u>RR #1</u>		<u>pg 40</u>	<u>land out 1833 Sec Thomas Rd</u>
	<u>RR #3</u>		<u>pg 383</u>	<u>Imp. 1903 Sec Selsor Moon Rd Imp</u>

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
<u>1908</u>			<u>Dorn Rd Imp. RR #4 pg 240</u>
<u>1955</u>	<u>Asph #46 stone</u>	<u>County</u>	<u>Road bed built up to 8" and black topped.</u>

IMPROVEMENTS Cont.

YEAR	TYPE OF	APPLIED BY	REMARKS
1957	Asph & 46 stone	County	Sealed from CR #78 to CR 77 (Prairie Pike)
1958	MCB & 6 stone	"	Spot sealed
MAY 1960	T-35	"	BROKEN PARTS OF ROAD REPAIRED AND SPOT SEALED
1960	M.C. 5 & 6 STONE	"	SURFACE SEALED IN STOKES TWP. —
1962	MC 5 & 6 stone	"	" treated from Prairie Pike to Fayette Co line (16.1 m)
1963	" "	"	" treated from ^{SR} 323 to CR 77 (Prairie Pike)
1966	MC 5 & #6 Stone	County	Surface treated
1969	MS & #4 Stone	County	Surface treated
1972	RS-2 & #8 Limestone	County	Surface treated
1975	9,616 GAL. RS2	VAN CAMP & COUNTY	SURFACE TREATED - 406.50 TONS #8 GRAVEL
1978	10,600 GAL. RS2 534.00 TON #8	HENSLEY	SURFACE TREATED - 353.80 TONS #8 GRAVEL
1982	10,034 GAL. RS2	BUCKEYE	SURFACE TREATED
1985	RS2 & #8 STONE	KOCK & NORTHWOOD	10,386 GAL. RS2 - 371.00 TON #8 - SPRINGFIELD
1990	11148.18 gal. liquid asphalt 484 tons #8	County	Surface treated - entire road sections A & B
1996	CRS2P #8 Limestone	County	Chip Seal 12065 Gal 192 Gal
2000	CRS2P #8 Stone	County	Chip seal 23,293 gal. Total. 927 tons. Both A & B