IMPROVED	MADIS		ROAD RECORD	BUS BLANK BOOK MFG. CO., COL., O. 5908				
Township A. A. S. A. A.	.UARBY A	vo5 <u>.</u> U_	CL:-	Sec. A (From 5 to 7) ping Point				
	11			·				
Class of Traffic	HEAVY			Distance				
Built by		Date	882	Price \$ 4485 **				
Surveyed by J. Converse								
BRICK .	CONCR	ETE	SLAG-LIMESTONE	GRAVEL '				
Kind of foundation	Thickness		(Filler) Center					
Thickness of foundation.	azina or cemene		Bottom Thickness Center	Width				
Make of brickWidth	DWITE		Size	:::: Crown6				
Crown	(Grave)			Cu, yas, Mat. 1000 p. P. at.				
Cushion	Stone		Binder	····				
Filler Kind of curb	Crown		Binder, Method					
Size of curbX	Kind of)	Width					
_ yds brick	expansion joints		Crown					
Cu. yds of base	Cu. yds. concrete		Cu. yds. Mat					
GENERAL Converse Hoth Road - 50.								
Total length 5.86	(2,75) miles.	Distance berm	to berm 26'	Width of R. W 50'				
Distance C. to C. Ditch		No. of steel bridges		No. Con. bridges				
No. of stone culverts		No. concrete culverts		No. of wood bridges				
No. of C. I. P		No. of cor. pipe		Total excavation				
Depth of Ditches		Has location been changed 119		Location on R. W. N. OF.				

INSPECTION OF IMPROVED ROADS.

Date of Inspection				•	
BRICK					
Condition of brick					<u> </u>
Condition of filler					
Condition of curb					
CONCRETE					
Condition of concrete			<u></u>		
Condition of surface	;				
SLAG-LIMESTONE					
Condition of foundation					
Condition of top					
Does top need to be scarified					
Are there ruts in road					
GRAVEL					
Condition of surface					<u> </u>
Is road ruted		1			
GENERAL					
Condition of ditches				1	
Condition of berms					
Rer: Laid out in 1821. See Ruppell's Road	4" Bood Bosout Ma	l nece 21 Alt and		92 See D T 22 S	1
Ter . Law out in 18 11 3 65 NOPPE 11'S MOO	N HOUR VECHEN HE	Harde El'union	mb. mbrosed 19	Or 205 M'T'W'I	10.1, page 235