

MADISON COUNTY HIGHWAYS

286

NO.	SECTION (S)	NAME	
75		Counts Rd	
Twp Rd.	FROM	Junction SR #38	TO Junction C-8 (Bloomington Pike)
	LENGTH	14837	(IN FEET) MILES 2.86
	PAVEMENT TYPE	Bit. Surf. Treat. & Gravel	WIDTH 16
	WIDTH OF R OF W	40	WIDTH OF BERMS 2
	TWP.	Range	MILES 2.86 TWP.
	REMARKS	Bit. Surf. treated to Junction T-76 from SR #38	

TOWNSHIP ROAD HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	RR #1		185	Laid out 1874 see here Counts Rd

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1955	Blacktopped	County	Road bed built up to 8" Primed and sealed with #46 Stone from SR #38 to Junction T-76



IMPROVEMENTS Cont. ^{75 2.86}

YEAR	TYPE OF	APPLIED BY	REMARKS
1956		County	Brimso ditches cut from Jct T-76 to Jct CR #8
1957	MCS 2 #6 stone	"	Road primed and sealed with #6 stone
			from T-76 to CR #8.
MAY 1960	T-35	"	BROKEN PARTS OF ROAD REPAIRED AND SPOT TREATED
1960	MCS #6 STONE	"	SURFACE SEALED ENTIRE LENGTH
1963	"	"	Surface treated
1966	MCS 2 #6 stone	County	Surface treated
1970	TAR #6 STONE	COUNTY	SURFACE TREATED
1973	RS25 #8 stone	County	Surface treated
1977	10,465 Gal. RS2	County - V.C.	Surface treated - 478.65 ton H.S. #8
1980	377,064 tons #8 9,482 Gal. RS2	County W.K. Co.	Surface Treated
1983	393.95 ton #8 8,922 Gal. RS2	County	Surface Treated (J.R. #38 to C.R. #8)
1986	872,240 ton #8 9,857 Gal. RS2	COUNTY Koch LUKK	SURFACE TREATED
1989	7684.93 gal. RS2 308 ton #8	County	Surface treated SR. 38 to CR 8
1998	Chip & Seal	County	11,549 Gal CRS2P, 378 Ton #8 Limestone
2003	Chip & Seal	County	10,212 Gal CRS2P 284 Ton #8 Limestone