| TOOKY ROAD THE COLUMBUS BLANK BOOK MFG. CO., COL., O. 5908 IMPROVED MADISON CO. ROAD RECORD | | | | | | | |
|--|--|---|---|--|--|--|--|
| Township STOKES | No 87 - | | Sec | | | | |
| Shipping Point | | | | | | | |
| Class of Traffic Lie | THE | • | Distance | | | | |
| Built by | Date | | Price \$ | | | | |
| Surveyed by | | | 1 | | | | |
| BRICK Kind of foundation Thickness of foundation Make of brick Width Crown Cushion Filler Kind of curb Size of curb X yds brick Cu. yds of base | | SLAG—LIMESTONE Filler Filler Center Edge Binder Filler Edge Thickness Center Edge Thickness Center Edge Filler Size Edge Binder Method Width Crown Cu. yds. Mat. | WidthCrownCu. yds, Mat. | | | | |
| Total length Z.OO Distance C. to C. Ditch No. of stone culverts No. of C. I. P. Depth of Ditches | No. of steel by No. concrete No. of cor. p | to berm | Width of R. W No. Con. bridges No. of wood bridges Total excavation Location on R. W. | | | | |

INSPECTION OF IMPROVED ROADS.

| Date of Inspection | , | | • • • | | <u> </u> |
|--|----------|----------|---------|----------|----------|
| BRICK | - | | | • | |
| Condition of brick | | | | | <u> </u> |
| Condition of filler | | | | | |
| Condition of curb | , | | | | |
| CONCRETE | | | | | |
| Condition of concrete | - | | | | |
| Condition of surfaceSLAG—LIMESTONE Condition of foundation | | | | -, . | |
| Condition of top | | | | | |
| Does top need to be scarified | | | | | |
| Are there ruts in road | | | <u></u> | <u> </u> | <u> </u> |
| GRAVEL Condition of surface | | | | | |
| Is road ruted | | | | | |
| GENERAL Condition of ditches | | | | | - |
| Condition of berms | | | | | |
| | <u> </u> | <u> </u> | | | |