

MADISON COUNTY HIGHWAYS

3.17

NO. <u>64</u>	SECTION (S)	NAME <u>McGuire</u>
FROM <u>Junction SR #665</u> TO <u>Junction C-22 (W. H. - Rousv.)</u>		
LENGTH <u>15474</u> (IN FEET) <u>3.12</u> MILES <u>3.17</u>		
PAVEMENT TYPE <u>Gravel</u> WIDTH <u>16</u>		
WIDTH OF R OF W <u>40</u> WIDTH OF BERMS <u>3</u>		
TWP <u>Fairfield</u> FEET <u>15474</u> MILES <u>3.12</u> TWP. <u>3.17</u> FEET _____ MILES _____		
REMARKS <u>COUNTY ROAD</u>		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
				Original Twp Rd - Home Rd
	R. Imp R #3	134		Imp 1897

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1955		County	Borers cut & entire road ditched and bore built up

IMPROVEMENTS Cont.

64

3.17

YEAR	TYPE OF	APPLIED BY	REMARKS
1956	Tar & #4 stone	County	Road primed & sealed with Tar & #4 stone
1957	MS & 6 stone	"	Road sealed with MC5 & #6 limestone
MAY 1960	T-35	"	BROKEN PARTS OF ROAD REPAIRED AND SPOT TREATED
1960	TAR & #6 STONE	"	SURFACE SEALED ENTIRE LENGTH
1963	" "	"	Surface treated
1966	Tar & #6 Stone	County	Surface treated
1969	Tar & #6 Stone	County	Surface treated
1972	RS-2 & #8 Dimestone	County	Surface treated
1974	11,506 Gal. RS-2	County	Surface treated - 351.50 ton #8 gravel
1977	13,899 Gal. RS-2	County - V.C.	Surface treated - 450.40 ton #8 gravel
1980	482.20 tons #8 10,687 Gal. RS-2	County W.R.W.	Surface treated
1983	510 tons #8 9,305 Gal. RS-2	County	Surface treated (S.R. 665 to C.R. #22)
1986	452.00 tons #8 10,676 Gal. RS-2	County KOCH & WKK	SURFACE TREATED
1996	CRS-2P #8 Limestone	County	Chip Seal Resurface 12,066 Gal 424 Ton
2000			Chip & Seal
2007			chip & Seal
2012			Chip & Seal