

IMPROVED

Middle Pike
MADISON CO. ROAD RECORD

Township JEFFERSON ⁴⁰⁰ CANAAN ⁰⁶⁰No. 10-C

Sec. _____

Shipping Point _____

Class of Traffic HEAVY

Distance _____

Built by _____

Date 1869Price \$ 3221 ²¹ per miSurveyed by J. A. F. Nett

BRICK

Kind of foundation _____
 Thickness of foundation _____
 Make of brick _____
 Width _____
 Crown _____
 Cushion _____
 Filler _____
 Kind of curb _____
 Size of curb X _____
☐ yds brick _____
 Cu. yds of base _____

CONCRETE

Thickness _____
 Kind of Cement _____
 Mixture _____
 Material ☐ Gravel _____
 ☐ Slax _____
 ☐ Stone _____
 Width _____
 Crown _____
 Kind of expansion joints } _____
 Cu. yds. concrete _____

SLAG—LIMESTONE

Bottom { Filler _____
 Thickness } Center _____
 Binder } Edge _____
 Size _____
 Top Course { Thickness } Center _____
 Filler _____
 Size _____
 Binder _____
 Binder, Method _____
 Width _____
 Crown _____
 Cu. yds. Mat. _____

GRAVEL

Thickness 12"
 Width 13'
 Crown 8"
 Cu. yds. Mat. _____

Length Constructed
Part in corp.5.23
.38

GENERAL

Total length 4.60 4.85 miles.
 Distance C. to C. Ditch _____
 No. of stone culverts 4
 No. of C. I. P. 3
 Depth of Ditches 2 1/2 (min)
 No. V. Pipe 4

Distance berm to berm 24
 No. of steel bridges 1
 No. concrete culverts 4
 No. of cor. pipe _____
 Has location been changed No

Width of R. W. 45'
 No. Con. bridges _____
 No. of wood bridges _____
 Total excavation _____
 Location on R. W. Center

INSPECTION OF IMPROVED ROADS.

Date of Inspection					
BRICK					
Condition of brick					
Condition of filler					
Condition of curb					
CONCRETE					
Condition of concrete					
Condition of surface					
SLAG—LIMESTONE					
Condition of foundation					
Condition of top					
Does top need to be scarified					
Are there ruts in road					
GRAVEL					
Condition of surface					
Is road rutted					
GENERAL					
Condition of ditches					
Condition of berms					