IMPROVED Township Some REOR	Potee 5 MADISON CO. I	ROAD RECORD	Sec.
Class of Traffic		Ship	ping Point Distance Price \$
Surveyed by			
BRICK Kind of foundation Thickness of foundation Make of brick Width Crown Cushion Filler Kind of curb Size of curb Jyds brick Cu. yds of base	Mixture Material { Sinx	SLAG—LIMESTONE Filter	Thickness Width Crown Cu, yds, Mat.
Total length 1.20 Distance C. to C. Ditch No. of stone culverts No. of C: I. P. Depth of Ditches	miles. Distance bern No. of steel b No. concrete No. of cor. r	ridges culverts	Width of R. W

INSPECTION OF IMPROVED ROADS.

Date of Inspection			•		
BRICK					
Condition of brick					1
Condition of filler		•		· · · · · ·	<u> </u>
Condition of curb					<u> </u>
CONCRETE					
Condition of concrete					<u> </u>
Condition of surface					
SLAG—LIMESTONE				i	,
Condition of foundation		3			
Condition of top					<u> </u>
Does top need to be scarified			<u> </u>	<u></u>	
Are there ruts in road				·	<u> </u>
GRAVEL	·				
- Condition of surface				<u> </u>	<u> </u>
Is road ruted					<u> </u>
. GENERAL		i		1	
Condition of ditches				 	<u> </u>
Condition of berms					1
	1	<u> </u>	<u> </u>	<u> </u>	<u> </u>