

IMPROVED**Price - Hilliards Road
MADISON CO. ROAD RECORD**Township CANAANNo. 32 - CSec. A
Fr. Co. Line to Jc. No. 7

Shipping Point _____

Class of Traffic _____

Distance _____

Built by _____

Date 1876Price \$ 563⁰⁰Surveyed by J. Arnett

| BRICK | CONCRETE | SLAG—LIMESTONE | GRAVEL |
|------------------------------------|----------------------------------|---------------------------------------|----------------------------------|
| Kind of foundation _____ | Thickness _____ | Bottom { Filler _____ | Thickness <u>12"</u> |
| Thickness of foundation _____ | Kind of Cement _____ | Bottom { Thickness } Center _____ | Width <u>13'</u> |
| Make of brick _____ | Mixture _____ | Bottom { Binder _____ | Crown <u>4"</u> |
| Width _____ | Material { Gravel _____ | Bottom { Size _____ | Cu. yds. Mat. <u>2542 p. mi.</u> |
| Crown _____ | Material { Slag _____ | Top Course { Thickness } Center _____ | |
| Cushion _____ | Material { Stone _____ | Top Course { Filler _____ | |
| Filler _____ | Width _____ | Top Course { Size _____ | |
| Kind of curb _____ | Crown _____ | Top Course { Binder _____ | |
| Size of curb <u>X</u> | Kind of expansion joints } _____ | Binder, Method _____ | |
| <input type="checkbox"/> yds brick | Cu. yds. concrete _____ | Width _____ | |
| Cu. yds of base _____ | | Crown _____ | |
| | | Cu. yds. Mat. _____ | |

GENERALTotal length 0.58 miles.

Distance C. to C. Ditch _____

No. of stone culverts _____

No. of C. I. P. _____

Depth of Ditches 2' min.Distance berm to berm 24'

No. of steel bridges _____

No. concrete culverts _____

No. of con. pipe _____

Has location been changed NoWidth of R. W. 45'

No. Con. bridges _____

No. of wood bridges _____

Total excavation _____

Location on R. W. Center

INSPECTION OF IMPROVED ROADS.

| | | | | | |
|------------------------------------|--|--|--|--|--|
| Date of Inspection_____ | | | | | |
| BRICK | | | | | |
| Condition of brick_____ | | | | | |
| Condition of filler_____ | | | | | |
| Condition of curb_____ | | | | | |
| CONCRETE | | | | | |
| Condition of concrete_____ | | | | | |
| Condition of surface_____ | | | | | |
| SLAG—LIMESTONE | | | | | |
| Condition of foundation_____ | | | | | |
| Condition of top_____ | | | | | |
| Does top need to be scarified_____ | | | | | |
| Are there ruts in road_____ | | | | | |
| GRAVEL | | | | | |
| Condition of surface_____ | | | | | |
| Is road rutted_____ | | | | | |
| GENERAL | | | | | |
| Condition of ditches_____ | | | | | |
| Condition of berms_____ | | | | | |

IMPROVED

Township CANAANPrice - Hilliards Road
MADISON CO. ROAD RECORDNo. 32-C

THE COLUMBUS BLANK BOOK MFG. CO., COL., O. 5908

Sec. B
Jc. No. 7 to Jc. No. 5

Shipping Point _____

Class of Traffic _____

Distance _____

Built by _____

Date 1881. 1882Price \$ 10224.68Surveyed by J. Converse

| BRICK | CONCRETE | SLAG-LIMESTONE | GRAVEL |
|------------------------------------|---|--|----------------------|
| Kind of foundation _____ | Thickness _____ | Bottom { Filler _____ Thickness { Center _____ Edge _____ Binder _____ Size _____ | Thickness <u>10"</u> |
| Thickness of foundation _____ | Kind of Cement _____ | | Width <u>11"</u> |
| Make of brick _____ | Mixture _____ | | Crown <u>4"</u> |
| Width _____ | Material { Gravel _____ Slag _____ Stone _____ | Top Course { Thickness { Center _____ Edge _____ Filler _____ Size _____ Binder _____ | Cu. yds. Mat. _____ |
| Crown _____ | | | Width _____ |
| Cushion _____ | | | Crown _____ |
| Filler _____ | Width _____ | Binder, Method _____ | |
| Kind of curb _____ | Crown _____ | Width _____ | |
| Size of curb <u>X</u> | Kind of. expansion joints } _____ | Crown _____ | |
| <input type="checkbox"/> yds brick | | Cu. yds. Mat. _____ | |
| Cu. yds of base _____ | Cu. yds. concrete _____ | | |

| 5.00 | | GENERAL | 26' | 50' |
|---------------------------------|--|-------------------------------------|-----|-------------------------------|
| Total length <u>5.00</u> miles. | | Distance berm to berm <u>26'</u> | | Width of R. W. <u>50'</u> |
| Distance C. to C. Ditch _____ | | No. of steel bridges _____ | | No. Con. bridges _____ |
| No. of stone culverts _____ | | No. concrete culverts _____ | | No. of wood bridges _____ |
| No. of C. I. P. _____ | | No. of cor. pipe _____ | | Total excavation _____ |
| Depth of Ditches <u>2' min.</u> | | Has location been changed <u>No</u> | | Location on R. W. <u>Side</u> |

INSPECTION OF IMPROVED ROADS.

| | | | | | |
|-------------------------------|--|--|--|--|--|
| Date of Inspection | | | | | |
| BRICK | | | | | |
| Condition of brick | | | | | |
| Condition of filler | | | | | |
| Condition of curb | | | | | |
| CONCRETE | | | | | |
| Condition of concrete | | | | | |
| Condition of surface | | | | | |
| SLAG—LIMESTONE | | | | | |
| Condition of foundation | | | | | |
| Condition of top | | | | | |
| Does top need to be scarified | | | | | |
| Are there ruts in road | | | | | |
| GRAVEL | | | | | |
| Condition of surface | | | | | |
| Is road rutted | | | | | |
| GENERAL | | | | | |
| Condition of ditches | | | | | |
| Condition of berms | | | | | |

Ref. Laid out 1832. See Harris' Rd. Rec. Vol. page 35
 Improved 1881-1882 See Rd. Imp. Rec. page 182 & 198