

MADISON COUNTY HIGHWAYS

3.62

NO. 56	SECTION (S) A	NAME Woods-Opossum Run
FROM Junction C-54 (Kioush-Palesine) TO Junction C-⁵⁵ (Anderson-Antioch)		
LENGTH 11246 1077 (IN FEET) MILES 2.13 2.04		
PAVEMENT TYPE Bit. Surf. Treated Gravel WIDTH 14		
WIDTH OF R OF W 40 WIDTH OF BERMS 2		
FEET 11246 FEET		
TWP Pleasant MILES 2.13 TWP. MILES		
REMARKS 2.31 - COUNTY - 4.85 - TOWNSHIP		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	RR #1		51	Laid out 1836 see Worthington Rd
	Rd. Imp. R #3		249	Impr. 1898 " O'Pos. Ru. Jk. Rd

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1958		County	Birms & ditches cut. Road bed built up Road primed & sealed with #46 stone



IMPROVEMENTS Cont.

YEAR	TYPE OF	APPLIED BY	REMARKS
1958	1423# 6 stone	County	Spot sealed
1959	Mc 2 6 stone	"	Surface treated
MAY 1960	T-35	"	BROKEN PARTS OF ROAD REPAIRED AND SPOT TREATED
1962	Tar & 6 stone	"	Surface treated
1965	TAR & 6 stone	COUNTY	SURFACE TREATED
1968	Tar & 6 stone	County	Surface treated
1971	R.S. 21# 8 stone	County	Surface treated
1974	8,152 Gal. RS25	County	Surface treated - 283.00 ton #8 gravel
1977	9,166 Gal. RS2	County - V.C.	Surface treated - 276.10 ton #8 gravel
1980	7,624 Gal. RS2	County W.K.W.	Surface treated
1983	322 tons #8 6,438 Gals. RS2	County	Surface treated (C.R. #54 to C.R. #59)
1986	3,560 TON #8 6,821 GAL. RS2	COUNTY KOCH & W.K.W.	SURFACE TREATED - (COUNTY END)
1986	32.00 TON #8 1,650 GAL. RS2	COUNTY KOCH & W.K.W.	SURFACE TREATED - (C.R. 54 TO END) (PLEASANT TWP.)
1996	CRS2P-#8 stone	County	Chip Seal 8,218 Gal 286 Ton
2000	CRS2P/#8 stone	county	chip seal 8094 gal 312 ton

MADISON COUNTY HIGHWAYS

NO. T-56 SECTION (S) 13 NAME Woods-O'Possum 1

FROM junction C-57-McClim.-Cemetery TO junction C-54 (Kiousv-Palestine)

LENGTH 8923 8342 (IN FEET) MILES 1.69 1.58

PAVEMENT TYPE Gravel Chip Seal WIDTH 14

WIDTH OF R OF W 40 Blacktop WIDTH OF BERMS 2

FEET 8923 FEET 1.58

TWP Pleasant MILES 1.69 TWP. MILES TWP. MILES

REMARKS 2.31-COUNTY - 1.85-TOWNSHIP

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
				see sect. A.

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1956		County	Bridges 46 ft and some slope applied. Bridge on N. end widened and new flow constructed

IMPROVEMENTS Cont.

YEAR	TYPE OF	APPLIED BY	REMARKS
MAY 1960	T-35	COUNTY	BROKEN PARTS OF ROAD REPAIRED AND SPOT TREATED
1965	MC5 ^{1/2} #6 STONE	COUNTY	SURFACE TREATED - Resealed ^{5 mile} next floor
1966	MC5 ^{1/2} #6 stone	County	Surface treated
1969	Tare #6 stone	County	Surface treated
1971	RS ^{1/2} #8 stone	County	Surface treated - 1 mile
1973	RS ^{1/2} #8 stone	County	Surface treated
1975	1,600 GAL RS-2	VAN CAMP & COUNTY	SURFACE TREATED (CULVERT TO END) 109.10 TONS #86 GRAVEL
1976	1,500 GAL RS-2	COUNTY	59.52 ton #8 gravel - (C.R. 57 to culvert)
1979	3,000 gal RS-2	Hensley	Surface treated (C.R. 57 to ^{END} culvert)
1983	^{126 ton #8} 3,595 Gal. RS-2	County	Surface Treated (C.R. #57 to C.R. #34)
1987	^{50.00 tons #8} 1,500 GAL RS-2	COUNTY & CENTRAL OIL	SURFACE TREATED - (C.R. 57 TO END)
1990	^{3800 gal. liq. road asphalt} ^{140 tons #8}	County	Surface treated (Pleasant Twp)
1991	^{18 tons #8} 776.56 gal CR52P	County	Surface treated (Sharp curve to Dead End) .20 mile
1996	402 asphalt	Northwood	Pave Leveling C. 9-14.419 Ton (CR57 To Bus Turnaround)
1996	404 asphalt	"	Pave Finish C. 475.83 Ton (CR57 To Bus Turnaround)
1996	617 Limestone	"	Berm 423.09 Ton (CR57 To Bus Turnaround)
1996	CR52P / #8 stone	County Road Crew	Chip Seal. 3,500 Gal; 129 Ton (CR57 To Creek)

MADISON COUNTY HIGHWAYS

NO. T-56	SECTION (S) B	NAME Woods - O Possum
FROM _____ TO 1.58		
LENGTH _____ (IN FEET) MILES _____		
PAVEMENT TYPE _____ WIDTH _____		
WIDTH OF R OF W _____ WIDTH OF BERMS _____		
TWP. _____ FEET _____ FEET _____ FEET _____		
MILES _____ MILES _____ MILES _____		
REMARKS _____		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1998	Chip & Seal	County	1078 Sal CRS2P, 32 Ton (CR-54) To Creek
1999	Dorm	County	Tons 4-11 Stone (CR-57 To Creek)

(SEE OTHER SIDE)

IMPROVEMENTS Cont.

[illegible]

MADISON COUNTY HIGHWAYS

0.80

NO. 57	SECTION (S)	NAME McClimansville-Cemetery
FROM Junction SR #56		TO Junction C-50 (Col-Wash. C.H.)
LENGTH 6230 6864		(IN FEET) MILES 1.18 1.30
PAVEMENT TYPE Bit. Surf. treated		WIDTH 18'
WIDTH OF R OF W 40'		WIDTH OF BERMS 4
TWP Pleasant		MILES 1.30
REMARKS COUNTY ROAD		

HISTORY

PETITIONED	ROAD RECORD BOOK	COMM. VOL.	JOURNAL PAGE	REMARKS
	RR #1		51	land out 1836 see Worthington Rd

IMPROVEMENTS

YEAR	TYPE OF	APPLIED BY	REMARKS
1952	Tare "6 shoe	County	Surface treated.
1957	" "	"	" "



IMPROVEMENTS Cont.

0.40

[illegible]