

IMPROVED

MADISON CO. ROAD RECORD

Township Monroe, Candan & Darby No. 125

Sec. 2 & 6

Class of Traffic Heavy

Shipping Point _____

Distance _____

Built by _____

Date 1889

Price \$ _____

Surveyed by _____

BRICK	CONCRETE	SLAG—LIMESTONE	GRAVEL
Kind of foundation _____	Thickness _____	Bottom { Filler _____ Thickness } Center _____ Binder _____ Size _____	Thickness <u>12" & 10"</u>
Thickness of foundation _____	Kind of Cement _____		Width <u>11"</u>
Make of brick _____	Mixture _____		Crown _____
Width _____	Material { Gravel _____ Slag _____ Stone _____	Top Course { Thickness } Center _____ Filler _____ Size _____ Binder _____	Cu. yds. Mat. _____
Crown _____			Binder, Method _____
Cushion _____			Width _____
Filler _____	Crown _____	Crown _____	
Kind of curb _____	Kind of expansion joints } _____ _____	Crown _____	
Size of curb _____ X _____		Cu. yds. Mat. _____	
<input type="checkbox"/> yds brick _____			
Cu. yds of base _____	Cu. yds. concrete _____		

GENERAL

Total length 4.50 miles.
 Distance C. to C. Ditch _____
 No. of stone culverts V. Pipe 10
 No. of C. I. P. 2
 Depth of Ditches _____

Distance berm to berm 24'
 No. of steel bridges _____
 No. concrete culverts 1
 No. of cor. pipe _____
 Has location been changed _____

Width of R. W. 50'
 No. Con. bridges _____
 No. of wood bridges _____
 Total excavation _____
 Location on R. W. _____

INSPECTION OF IMPROVED ROADS.

Date of Inspection					
BRICK					
Condition of brick					
Condition of filler					
Condition of curb					
CONCRETE					
Condition of concrete					
Condition of surface					
SLAG—LIMESTONE					
Condition of foundation					
Condition of top					
Does top need to be scarified					
Are there ruts in road					
GRAVEL					
Condition of surface					
Is road rutted					
GENERAL					
Condition of ditches					
Condition of berms					