

DEED REFERENCES USED

D.B.	Pg.
23	54
185	42
95	27
247	30B
259	585
258	09
248	80
188	20Z
185	38
256	166
209	02
243	46
210	44

ALSO D.B. 188 Pg. 20Z
AND AERIAL N° 2 OF 107

I HEREBY CERTIFY THAT I HAVE PERSONALLY MADE A CURRENT FIELD SURVEY OF THE BOUNDARY LIMITS DELINEATED HEREON — IN ACCORDANCE WITH THE MINIMUM STANDARD DETAIL REQUIREMENTS AS SET FORTH IN THE OHIO ADMINISTRATIVE CODE.

BASIS FOR BEARINGS DERIVED FROM CURRENT DEED OF RECORD IN D.B. 185 PG. 42 ALL CORNER MARKERS WERE SET AND/OR FOUND WHILE MAKING THIS SURVEY — EACH CORNER SHOWN IS AS CURRENTLY MARKED. THE POINTS WITHIN THE OPEN FLOWING DITCH WERE NOT SET BUT REFERENCED TO A ON SITE 20 FT. OFF-SET TRAVERSE WITH TRAVERSE POINTS MARKED WITH 3/4" IRON PIPE.

IN MY OPINION THIS PLAT IS TRUE AND CORRECT TO THE BEST OF MY BELIEF.

Rodger Irwin Baker MARCH 21ST 1986
RODGER IRWIN BAKER, OHIO LIC. N° S-05539
2121 U. S. RT. 42 S.W. LONDON, OHIO 43140

PLAT OF A FIELD SURVEY MADE IN MAR. 1986 BEING 0.015 AC., 29.889 AC. AND 20.096 AC. A TOTAL PERIMETER OF 50.000 ACRES LOCATED IN VMS 7398 & 7823 AMITY PIKE, DARBY TWP. AND CANAAN TWP., MADISON CO. STATE OF OHIO

SCALE: 1"=100'

LANDS OF CHAUNCY HEADINGS & GERTIE HEADINGS PARTS OF 1.00 AC., 29.498 AC. AND 70.502 AC.

