

H.L. & D.M. SIEBOLD  
DB 145 P 69

FD IP AT ANGLE POINT  
IN MANSFIELD SIEBOLD LINE

EXISTING FARM FENCE  
N 46° 43' 05" E 435.60'

FD SPK 2' DEEP

SET IP

25.01'

N. OR NE CORNER  
OF 16.440 AC.  
MANSFIELD TRACT

150.00'  
S 44° 34' 36" E

TAYLOR BLAIR ROAD

H.L. & D.M. SIEBOLD  
DB 145 P 69

N 44° 34' 36" W  
150.00'

SET IP

OF SWALE  
1.500 ACRES

S 46° 43' 05" W 435.60'

25.01'

SET IP

SET  
PONY  
SPIKE

V.L. MANSFIELD  
DB 228 P 30


PLAT OF SURVEY  
OF A 1.500 ACRE TRACT  
VMS 2682 JEFFERSON TWP  
MADISON CO. OHIO

FOR ROSANNA & RON MANSFIELD

ALL POINTS MARKED SET IP, ARE 5/8" x 30" REBAR  
WITH YELLOW PLASTIC CAP MARKED "THOMAS ENGR.  
& SURVEYING"

SURVEYED OCTOBER 1987

THE THOMAS ENGINEERING & SURVEYING CO.  
COLUMBUS, OHIO



*Robert G. Watts*  
ROBERT G. WATTS REG. SURVEYOR #4138

17-93