

Paul R. Clapsaddle, P.E., P.S.

Proj: shrokb98 Dwg: shrokb304 Scale: 1" = 240' Date: March 4, 2004

## SURVEY FOR EMMETT SCHROCK 32.892 Acres March 4, 2004

The following described 32.892 acre tract is situated in the State of Ohio, County of Madison, Township of Jefferson, V.M.S. 7829, V.M.S. 12918, V.M.S. 8926, 8927 & 9391, being part of Emmett M. Schrock's 169.152 acre Tract L described in Official Record 98, page 1717, said 32.892 acre tract being more particularly described as follows:

Beginning at a 1 inch iron pin in a monument box found at the intersection of the centerline of State Route #29 (60 feet wide) with the centerline of State Route #42 (60 feet wide), said pin marking an east corner of said 169.152 acre tract and the place of beginning:

Thence South 41°40'00" West (assumed bearing) 1324.08 feet, following the centerline of State Route #42 and a southeast line of said 169.152 acre tract, to a magnetic nail set at the east corner of LeMitco, LLC's 10.438 acre tract described in Official Record 134, page 469;

Thence North 48°19'50" West 1155.05 feet, departing from the centerline of said Road and following the northeast line of said 10.438 acre tract and a southwest line of said 169.152 acre tract, passing at 29.98 feet a 5/8 inch iron pin found, to an iron pin set;

Thence North 41°40'00" East 1156.84 feet, departing from the north corner of said 10.438 acre tract and crossing said 169.152 acre tract, passing at 1126.53 feet an iron pin set, to a magnetic nail set in the centerline of State Route #29;

Thence South 56°34'10" East 1167.09 feet, following the centerline of said Road and a northeast line of said 169.152 acre tract, to the place of beginning, containing 32.892 acres, more or less, and being subject to all valid easements and restrictions of record.

Of the above described 32.892 acre tract, 1.769 acres are in V.M.S. 12918, 17.572 acres are in V.M.S. 7829, and 13.551 acres are in V.M.S. 8926, 8927 & 9391.

The above description was prepared from a field survey made under the supervision of Paul R. Clapsaddle, Registered Surveyor #6140, during the month of March 2004. Bearings indicated hereon are based on an assumed meridian with all others based on angles turned. Iron pins set are 5/8 inch by 30 inch reinforcing rods with caps marked "CLAPSADDLE RS #6140".

ATTEST:

Paul R. Clapsaddle, R.S. #6140

19019 West Darby Road, Marysville, Ohio 43040

(937) 747-2599