

MCCARTY ASSOCIATES, LLC

ARCHITECTS—ENGINEERS—SURVEYORS

HILLSBORO WASHINGTON C.H.

LOVELAND

213 N. HIGH ST., HILLSBORO, OHIO 45133 PH 937-393-9971 FAX 937-393-2480 Michael L. McCarty, P.E., P.S.— Thomas E. Purtell, P.S.— Loren M. Puckett, P.E.— Eric N. Lutz, P.S.— Jerrold B. Bradley, AIA

File No. S10-806 November 22, 2010

LEGAL DESCRIPTION

David L. Katterhenrich, et al And Amber T. Bigam, et al 53.746 Acres Tract

Situated in the Township of Fairfield, County of Madison, State of Ohio, being a part of V.M.S. Nos. 5190 and 13816-13138, being all that remains of the original 84 acres "Lot No. 4" as conveyed to Amber T. Bigam and Apryl T. Flocken (one half interest) and recorded in Official Record 191, Page 1161, and one half interest conveyed to David L. Katterhenrich (50% interest), Alice Katterhenrich (12.50% interest), Beth Ann Katterhenrich (12.50% interest), and Laura Scheck (12.50% interest) and recorded in Official Record 249, Page 2596 of the Madison County Recorder's Office, and being further bounded and described as follows:

Beginning at a railroad spike (found) in the centerline of Nioga-Toops Road (County Road No. 60), said railroad spike being the southerly most corner of the 5.17 acres tract as conveyed to Robert F. Alberts, et al (O.R. 207, Page 2588);

thence with the centerline of Nioga-Toops Road S 56°52'45" W, a distance of 869.74 feet to a 5/8" iron pipe (found), said iron pipe being the easterly most corner of the 110.2031 acres tract as conveyed to Curtis Edward Cupp (O.R. 243, Page 1878);

thence with Cupp's northeasterly line N 34°24'17" W, passing a 5/8" iron pin (set) replacing a 5/8" iron pin (found, bent) at 25.00 feet, a total distance of 2751.67 feet to a 5/8"

iron pin (found) in the southeasterly line of the 49.65 acres "Tract IV" as conveyed to William Sherrill Hartford, et al (D.B. 278, Page 234);

thence with Hartford's southeasterly line N 61°26'23" E, a distance of 858.14 feet to a 5/8" iron pin (set), said iron pin being the westerly most corner of the 30.45 acres "Parcel No. Two, Tract 2" as conveyed to Robert Dale Timmons, et ux (O.R. 071, Page 372);

thence with Timmons' southwesterly line S 34°44'35" E, passing Timmons' southerly most corner and continuing with the southwesterly line of the 21.674 acres tract as conveyed to Aaron M. Stingle (O.R. 244, Page 1406), passing a 1" iron pipe (found) marking Stingle's corner at 1220.46 feet and continuing with the southwesterly line of a 5.660 acres tract as conveyed to Ralph Sparrow, et al (D.B. 290, Page 027), passing Sparrow's southerly most corner and continuing with the southwesterly line of a 5.17 acres tract as conveyed to Robert F. Alberts, et al (O.R. 207, Page 2588), passing a 5/8" iron pin (set) at 2658.82 feet, a total distance of 2683.82 feet to the beginning, containing 53.746 acres of land.

Subject to all legal easements and rights-of-way of record.

Bearings are based upon the Grid Azimuth (AZ. 357° 03′ 29.0″) between National Geodetic Survey Monuments "WE 1 FRA CO PIC CO MAD CO" and "FRA CO WE 20 MAD CO" and derived from GPS observations taken November 16, 2010, utilizing the Trimble ODOT CORS VRS (Virtual Reference System).

Land surveyed in November 2010, under the direction of Thomas E. Purtell, Registered Professional Surveyor No. 6519, the survey plat of which is referred to as Project No. S10-806 on file in the office of McCarty Associates, LLC, Washington C.H., Ohio.

All iron pins (set) are 5/8" diameter with 1-1/4" diameter plastic caps stamped "McCARTY ASSOCIATES".

Thomas E. Purtell, P.S. 6519

