

MCCARTY ASSOCIATES, LLC

ARCHITECTS—ENGINEERS—SURVEYORS

Hillsboro — Washington C.H. —

· LOVELAND

213 N. HIGH ST., HILLSBORO, OHIO 45133 PH 937-393-9971 FAX 937-393-2480
Michael L. McCarty, P.E., P.S.—Thomas E. Purtell, P.S.—Loren M. Puckett, P.E.—Eric N. Lutz, P.S.—Jerrold B. Bradley, AIA

File No. S11-781 August 3, 2011

LEGAL DESCRIPTION

Jackland, LLC
To
Raynor Farms, Inc.
25.243 Acres Tract

Situated in the Township of Union, County of Madison, State of Ohio, being a part of V.M.S. No. 7945-8448, being a part of the 146.776 acres tract as conveyed to Jackland, LLC and recorded in Official Record 211, Page 2141 of the Madison County Recorder's Office, and being further bounded and described as follows:

Commencing at a P.K. nail (found) marking the centerline intersection of Madden - Higgins Road (County Road No. 82) and Yankeetown - Chenoweth Road (County Road No. 9), said P.K. nail being the westerly most corner of the 146.776 acres tract of which this description is a part;

thence with the centerline of Yankeetown - Chenoweth Road S 34°58'59" E, a distance of 1168.82 feet to a Mag nail (set) marking the true point of beginning of the tract of land herein described;

thence with a new division line and the generally centerline of Madden Open Drainage Ditch for the next ten calls:

(1) N 36°01'15" E, passing a 5/8" iron pin (set) at 20.00 feet, a total distance of 118.02 feet to a point in said ditch from which a 5/8" iron pin (set) on the north side of said ditch bears N 54°14'10" E, a distance of 118.28 feet;

- (2) N 60°49'34" E, a distance of 135.97 feet to a point in said ditch from which a 5/8" iron pin (set) on the north side of said ditch bears N 82°51'40" E, a distance of 22.92 feet;
- (3) S 89°07'29" E, a distance of 260.24 feet to a point in said ditch from which a 5/8" iron pin (set) on the north side of said ditch bears N 78°41'33" E, a distance of 24.27 feet;
- (4) S 60°20'44" E, a distance of 341.33 feet to a point in said ditch from which a 5/8" iron pin (set) on the north side of said ditch bears N 02°53'30" E, a distance of 32.79 feet;
- (5) N 58°40'34" E, a distance of 142.43 feet to a point in said ditch from which a 5/8" iron pin (set) on the north side of said ditch bears \$ 71°00'37" W, a distance of 126.92 feet;
- (6) N 78°32'40" E, a distance of 161.76 feet to a point in said ditch from which a 5/8" iron pin (set) on the north side of said ditch bears N 10°17'43" E, a distance of 22.51 feet;
- (7) N 38°45'46" E, a distance of 725.19 feet to a point in said ditch from which a 5/8" iron pin (set) on the south side of said ditch bears S 50°23'44" E, a distance of 13.33 feet;
- (8) N 44°13'21" E, a distance of 583.78 feet to a point in said ditch from which a 5/8" iron pin (set) on the south side of said ditch bears S 03°30'16" W, a distance of 22.36 feet;
- (9) N 74°54'10" E, a distance of 844.26 feet to a point in said ditch from which a 5/8" iron pin (set) on the south

side of said ditch bears S 23°23'44" E, a distance of 10.77 feet;

(10) N 67°04'05" E, a distance of 131.77 feet to a point in the westerly line of the original 123.47 acres (net 80.2687 acres) "Tract I" as conveyed to Donald Hemmelgarn and Gale A. Heitkamp (O.R. 98, Page 1618);

thence Hemmelgarn's westerly line S 21°25'50" W, passing a 5/8" iron pin (set) at 24.11 feet, a total distance of 278.31 feet to a 5/8" iron pin (set) by a stone (found) by a post;

thence also Hemmelgarn's line S 54°57'30" W, passing.

Hemmelgarn's corner and continuing with the northwesterly line of an original 161.11 acres (net 157.50 acres) tract as conveyed to Raynor Farms, Inc., passing a 5/8" iron pin (set) at 2830.04 feet, a total distance of 2855.04 feet to a 1" iron pin (found) 9 inches under the pavement in the centerline of Yankeetown - Chenoweth Road;

thence with the centerline of Yankeetown - Chenoweth Road N 34°58'59" W, a distance of 669.14 feet to the true point of beginning, containing 25.243 acres of land.

Subject to an assessment for maintenance for the Madden Open Drainage Ditch No. 61.

Subject to all other legal easements and rights-of-way of record.

Bearings are based upon the Grid Azimuth (Az 152° 33′ 15.0″) between National Geodetic Survey and ODOT CORS Station "OHMD" and McCarty Associates Geodetic Survey Monument "JACKLAND (2001)" and derived from GPS observations taken August 2, 2011 and July 20, 2011, utilizing the Trimble ODOT CORS VRS (Virtual Reference System).

Land surveyed in August 2011, under the direction of Thomas E. Purtell, Registered Professional Surveyor No. 6519, the survey plat of which is referred to as Project No. S11-781 on file in the office of McCarty Associates, LLC, Washington C.H., Ohio.

All iron pins (set) are 5/8" diameter with 1-1/4" diameter plastic caps stamped "McCARTY ASSOCIATES".

Thomas E. Purtell, P.S. 6519

